

MINICUBE

Portable dimmer

DESCRIPTION

MINICUBE is a portable dimmer. One channel 3 Kw.
Equipped with a carrying handle and a thread pitch «M10»
for installation and truss with clamp. For halogen sources, halogen low
voltage and incandescent lamps.

FONCTIONS

- DMX address with 3 wheels
- Local control with rotary potentiometer
- Start phase-cut dimmer

CARACTERISTICS

Power supply (Vac)	230 +/- 10%
Fréquency (Hz)	50/60
Power rating halogen (W)	3 000
Power rating halogen TBT (W)	2 100
Efficiency (%)	98
Temperature (°C)	0 at 40
Humidy (%)	0 at 90
Protection degree (IP)	30
Cooling system	Natural convection
Isolated control of the network	yes
Output protection	Braker Uni + N, 16A
Internal protection	Against voltage surges

*Delivery with 1.5 m of cable



Height (mm)	130
Width (mm)	150
Depth (mm)	80
Weight (Kg)	1.50
Structure	Steel, Aluminium

Warning !

- This device does not allow a physical cut of lamps (Even when the level of remote control is 0).
- The output protection follow NFC 15-100.
- This device must be upstream protected by a differential protection 30 mA.
- The nominal value must be respected.
- This device is conceived to work on any private or public network and is intended for professional use.
- RVE SAS Reserve the right to bring, without preliminary opinion any modification in the specifications or the construction of the equipment describes.
- This dimmer follow the compatibility CEM : EN 55014 / 60669

FUNCTIONS

